

NAME

AutoLoader - load subroutines only on demand

SYNOPSIS

```
package Foo;
use AutoLoader 'AUTOLOAD';    # import the default AUTOLOAD subroutine

package Bar;
use AutoLoader;                # don't import AUTOLOAD, define our own
sub AUTOLOAD {
    ...
    $AutoLoader::AUTOLOAD = "...";
    goto &AutoLoader::AUTOLOAD;
}
```

DESCRIPTION

The **AutoLoader** module works with the **AutoSplit** module and the `__END__` token to defer the loading of some subroutines until they are used rather than loading them all at once.

To use **AutoLoader**, the author of a module has to place the definitions of subroutines to be autoloaded after an `__END__` token. (See *perldata*.) The **AutoSplit** module can then be run manually to extract the definitions into individual files *auto/functype.al*.

AutoLoader implements an AUTOLOAD subroutine. When an undefined subroutine is called in a client module of **AutoLoader**, **AutoLoader**'s AUTOLOAD subroutine attempts to locate the subroutine in a file with a name related to the location of the file from which the client module was read. As an example, if *POSIX.pm* is located in */usr/local/lib/perl5/POSIX.pm*, **AutoLoader** will look for perl subroutines **POSIX** in */usr/local/lib/perl5/auto/POSIX/*.al*, where the *.al* file has the same name as the subroutine, sans package. If such a file exists, AUTOLOAD will read and evaluate it, thus (presumably) defining the needed subroutine. AUTOLOAD will then `goto` the newly defined subroutine.

Once this process completes for a given function, it is defined, so future calls to the subroutine will bypass the AUTOLOAD mechanism.

Subroutine Stubs

In order for object method lookup and/or prototype checking to operate correctly even when methods have not yet been defined it is necessary to "forward declare" each subroutine (as in `sub NAME;`). See "*SYNOPSIS*" in *perlsub*. Such forward declaration creates "subroutine stubs", which are placeholders with no code.

The **AutoSplit** and **AutoLoader** modules automate the creation of forward declarations. The **AutoSplit** module creates an 'index' file containing forward declarations of all the **AutoSplit** subroutines. When the **AutoLoader** module is 'use'd it loads these declarations into its callers package.

Because of this mechanism it is important that **AutoLoader** is always `used` and not `required`.

Using AutoLoader's AUTOLOAD Subroutine

In order to use **AutoLoader**'s AUTOLOAD subroutine you *must* explicitly import it:

```
use AutoLoader 'AUTOLOAD';
```

Overriding AutoLoader's AUTOLOAD Subroutine

Some modules, mainly extensions, provide their own AUTOLOAD subroutines. They typically need to check for some special cases (such as constants) and then fallback to **AutoLoader**'s AUTOLOAD for the rest.

Such modules should *not* import **AutoLoader**'s AUTOLOAD subroutine. Instead, they should define their own AUTOLOAD subroutines along these lines:

```
use AutoLoader;
use Carp;

sub AUTOLOAD {
    my $sub = $AUTOLOAD;
    (my $constname = $sub) =~ s/.*:://;
    my $val = constant($constname, @_ ? $_[0] : 0);
    if ($! != 0) {
        if ($! =~ /Invalid/ || ${EINVAL}) {
            $AutoLoader::AUTOLOAD = $sub;
            goto &AutoLoader::AUTOLOAD;
        }
        else {
            croak "Your vendor has not defined constant $constname";
        }
    }
    *$sub = sub { $val }; # same as: eval "sub $sub { $val }";
    goto &$sub;
}
```

If any module's own AUTOLOAD subroutine has no need to fallback to the AutoLoader's AUTOLOAD subroutine (because it doesn't have any AutoSplit subroutines), then that module should not use **AutoLoader** at all.

Package Lexicals

Package lexicals declared with `my` in the main block of a package using **AutoLoader** will not be visible to auto-loaded subroutines, due to the fact that the given scope ends at the `__END__` marker. A module using such variables as package globals will not work properly under the **AutoLoader**.

The `vars` pragma (see "*vars*" in *perlmod*) may be used in such situations as an alternative to explicitly qualifying all globals with the package namespace. Variables pre-declared with this pragma will be visible to any autoloader routines (but will not be invisible outside the package, unfortunately).

Not Using AutoLoader

You can stop using AutoLoader by simply

```
no AutoLoader;
```

AutoLoader vs. SelfLoader

The **AutoLoader** is similar in purpose to **SelfLoader**: both delay the loading of subroutines.

SelfLoader uses the `__DATA__` marker rather than `__END__`. While this avoids the use of a hierarchy of disk files and the associated open/close for each routine loaded, **SelfLoader** suffers a startup speed disadvantage in the one-time parsing of the lines after `__DATA__`, after which routines are cached. **SelfLoader** can also handle multiple packages in a file.

AutoLoader only reads code as it is requested, and in many cases should be faster, but requires a mechanism like **AutoSplit** be used to create the individual files. *ExtUtils::MakeMaker* will invoke **AutoSplit** automatically if **AutoLoader** is used in a module source file.

Forcing AutoLoader to Load a Function

Sometimes, it can be necessary or useful to make sure that a certain function is fully loaded by AutoLoader. This is the case, for example, when you need to wrap a function to inject debugging

code. It is also helpful to force early loading of code before forking to make use of copy-on-write as much as possible.

Starting with AutoLoader 5.73, you can call the `AutoLoader::autoload_sub` function with the fully-qualified name of the function to load from its `.a/` file. The behaviour is exactly the same as if you called the function, triggering the regular `AUTOLOAD` mechanism, but it does not actually execute the autoloader function.

CAVEATS

AutoLoaders prior to Perl 5.002 had a slightly different interface. Any old modules which use **AutoLoader** should be changed to the new calling style. Typically this just means changing a `require` to a `use`, adding the explicit `'AUTOLOAD'` import if needed, and removing **AutoLoader** from `@ISA`.

On systems with restrictions on file name length, the file corresponding to a subroutine may have a shorter name than the routine itself. This can lead to conflicting file names. The *AutoSplit* package warns of these potential conflicts when used to split a module.

AutoLoader may fail to find the autosplit files (or even find the wrong ones) in cases where `@INC` contains relative paths, **and** the program does `chdir`.

SEE ALSO

SelfLoader - an autoloader that doesn't use external files.

AUTHOR

AutoLoader is maintained by the perl5-porters. Please direct any questions to the canonical mailing list. Anything that is applicable to the CPAN release can be sent to its maintainer, though.

Author and Maintainer: The Perl5-Porters <perl5-porters@perl.org>

Maintainer of the CPAN release: Steffen Mueller <smueller@cpan.org>

COPYRIGHT AND LICENSE

This package has been part of the perl core since the first release of perl5. It has been released separately to CPAN so older installations can benefit from bug fixes.

This package has the same copyright and license as the perl core:

```
Copyright (C) 1993, 1994, 1995, 1996, 1997, 1998, 1999,
2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009,
2011, 2012, 2013
by Larry Wall and others
```

All rights reserved.

This program is free software; you can redistribute it and/or modify it under the terms of either:

a) the GNU General Public License as published by the Free Software Foundation; either version 1, or (at your option) any later version, or

b) the "Artistic License" which comes with this Kit.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See either the GNU General Public License or the Artistic License for more

details. You should have received a copy of the Artistic License with this

Kit, in the file named "Artistic". If not, I'll be glad to provide one.

You should also have received a copy of the GNU General Public License along with this program in the file named "Copying". If not, write to the

Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA or visit their web page on the internet at <http://www.gnu.org/copyleft/gpl.html>.

For those of you that choose to use the GNU General Public License, my interpretation of the GNU General Public License is that no Perl script falls under the terms of the GPL unless you explicitly put said script under the terms of the GPL yourself. Furthermore, any object code linked with perl does not automatically fall under the terms of the GPL, provided such object code only adds definitions of subroutines and variables, and does not otherwise impair the resulting interpreter from executing any standard Perl script. I consider linking in C subroutines in this manner to be the moral equivalent of defining subroutines in the Perl language itself. You may sell such an object file as proprietary provided that you provide or offer to provide the Perl source, as specified by the GNU General Public License. (This is merely an alternate way of specifying input to the program.) You may also sell a binary produced by the dumping of a running Perl script that belongs to you, provided that you provide or offer to provide the Perl source as specified by the GPL. (The fact that a Perl interpreter and your code are in the same binary file is, in this case, a form of mere aggregation.) This is my interpretation of the GPL. If you still have concerns or difficulties understanding my intent, feel free to contact me. Of course, the Artistic License spells all this out for your protection, so you may prefer to use that.