

NAME

Pod::Perldoc::GetOptsOO - Customized option parser for Pod::Perldoc

SYNOPSIS

```
use Pod::Perldoc::GetOptsOO ();

Pod::Perldoc::GetOptsOO::getopts( $obj, \@args, $truth )
    or die "wrong usage";
```

DESCRIPTION

Implements a customized option parser used for *Pod::Perldoc*.

Rather like Getopt::Std's getopts:

Call Pod::Perldoc::GetOptsOO::getopts(\$object, \@ARGV, \$truth)

Given -n, if there's a opt_n_with, it'll call \$object->opt_n_with(ARGUMENT) (e.g., "-n foo" => \$object->opt_n_with('foo'). Ditto "-nfoo")

Otherwise (given -n) if there's an opt_n, we'll call it \$object->opt_n(\$truth) (Truth defaults to 1)

Otherwise we try calling \$object->handle_unknown_option('n') (and we increment the error count by the return value of it)

If there's no handle_unknown_option, then we just warn, and then increment the error counter

The return value of Pod::Perldoc::GetOptsOO::getopts is true if no errors, otherwise it's false.

SEE ALSO

Pod::Perldoc

COPYRIGHT AND DISCLAIMERS

Copyright (c) 2002-2007 Sean M. Burke.

This library is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

This program is distributed in the hope that it will be useful, but without any warranty; without even the implied warranty of merchantability or fitness for a particular purpose.

AUTHOR

Current maintainer: Mark Allen <mallen@cpan.org>

Past contributions from: brian d foy <bdfey@cpan.org> Adriano R. Ferreira <ferreira@cpan.org>, Sean M. Burke <sburke@cpan.org>